




מדינת ישראל
STATE OF ISRAEL




Handwritten mark resembling a stylized 'X' or '2' with a slash

Ministry of Justice
Patent Office

משרד המשפטים
לשכת הפטנטים

This is to certify that
annexed hereto is a true
copy of the documents as
originally deposited with
the patent application
of which particulars are
specified on the first page
of the annex.

זאת לתעודה כי
רצופים בזה העתקים
נכונים של המסמכים
שהופקדו לכתחילה
עם הבקשה לפטנט
לפי הפרטים הרשומים
בעמוד הראשון של
הנספח.



PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

This 7.5.11.2002 היום
רשם הפטנטים
Commissioner of Patents

נתאשר
Certified

לשימוש הלשכה
For office Use

חוק הפטנטים, תשכ"ז - 1967
PATENT LAW - 5727 - 1967

מספר: NUMBER	146462
תאריך: Date	13-11-2001
הוקדם/ נדחה ANTE/POST-DATED	

בקשה לפטנט
Application For Patent

אני, (שם המבקש, מענו ולגבי גוף מאוגד - מקום ההתאגדות)
I (Name and address of applicant, and in case of body corporate-place of incorporation

Karma Pharm Ltd.
35 Jabotinsky St.
Ramat Gan 52511
Israel

קרמה פארם בע"מ
35 ז'בוטינסקי
רמת גן 52511
ישראל

שם המצאה הוא
of an invention the title of which is

הדין

בעל אמצאה מכח
Owner, by virtue of
(בעברית)
(Hebrew)
(באנגלית)
(English)

תערוכות שחרור ממושכות המכילות כתובות פעילה ואנאלפאקסין הידרוכלוריד

Extended release compositions comprising as active compound Venlafaxine Hydrochloride

hereby apply for a patent to be granted to me in respect thereof.

מבקש בזאת כי ינתן לי עליה פטנט

*בקשה חלוקה- Division of Application		*בקשה פטנט מוסף- Addition Application for Patent		* דרישה דין קדימה Priority Claim		
מבקשת פטנט Application from No dated	מס מיום dated	לבקשה/לפטנט to Patent/Application No dated	מס מיום dated	מספר / סימן Number / Mark	תאריך Date	מדינת האגוד Convention Country
יפוי כח כללי / מיוחד - רצוף / נפרד to be filed later / attached - P.O.A.: general / individual הוגש בעניין filed in case						
המען למסירת מסמכים בישראל Address for service in Israel 9644 - זה						
Dr. Yitzhak Hess & Partners P.O.B. 6451 TEL AVIV 61063				ד"ר יצחק הס ושותפיו ת.ד. 6451 תל אביב 61063		
Signature of Applicant For the applicant: DR. YITZHAK HESS & PARTNERS BY :				שנת 2001 of the year		
				11 היום This		
				בחדש נובמבר of		
				לשימוש הלשכה For Office Use		

טופס זה כשהוא מוטבע בחותם לשכת הפטנטים ומושלם בספר ובתאריך ההגשה, הנו אישור להגשת הבקשה שפרטיה רשומים לעיל.
This form, impressed with the seal of the Patent Office and indicating the number and of filing, certifies the filing of the application the particulars of which are set out above

*Delete whatever is inapplicable - מחק את המיותר -


תערובות שחרור ממושכות המכילות כתרובת פעילה ואלאפאקסין הידרוכלוריד

Extended release compositions comprising as active compound Venlafaxine Hydrochloride

Karma Pharm Ltd.

The present invention relates to extended release compositions comprising as active compound Venlafaxine Hydrochloride.

Venlafaxine Hydrochloride is an antidepressant having formula 1



being designated (R/S)-1- [2-(dinehylamino) – 1 – (4- methoxyphenyl) ethyl] cyclohexanol hydrochloride or (\pm) – 1 – [a \downarrow (dimethylamino) methyl] p-methoxybenzyl cyclohexanol hydrochloride, having the empirical formula of C₁₇H₂₇NO₂ hydrochloride and molecular weight of 313.87.

Venlafaxine hydrochloride is a white to off white crystalline solid with a solubility of 572 mg/ml in water (adjustment to ionic strength of 0.2 M with sodium chloride). Its octanol: water (0.2 M sodium chloride) partition coefficient 0.43. Effexor XR the Brand product is formulated as an extended release capsule for once a day oral administration.

The drug release has so far been controlled by diffusion through the coating membrane on the spheroids and is not pH dependent. Known capsules containing Venlafaxine Hydrochloride comprise amounts equivalent to 37.5 mg, 75 mg, or 150 mg of Venlafaxine. The inactive ingredients are mainly cellulose, ethylcellulose, gelatin, hydroxypropyl methylcellulose, iron oxide, and titanium dioxide.

Controlled or extended release dosage forms of medicament are conventionally produced as hydrogel matrix based tablets. At this technology the controlled release dosage forms are simply prepared by mixing the active material with the appropriate rate of controlling polymers and then that mixture is compressed into the desired controlled release tablets. The rate controlling polymers are normally termed as hydrogels. Examples of such polymers are cellulose ethers such as ethyl cellulose or hydroxypropylcellulose. Patents describing preparation methods of such dosage forms are described for example in US Patent Specifications 4,966,768 or 4,389,393.

In some cases, for example with very water soluble active materials and with relatively high doses it is not feasible to produce tablets which enable appropriate control on the drugs release. This is the case, for example with Venlafaxine Hydrochloride.

In such a case a suitable approach is encapsulating the drug and producing extended release capsules dosage forms. When preparation of such dosage forms is considered, the preferred way is to mix the active ingredient with at least one binding agent to form a uniform mixture which is later moistened with water or with an appropriate organic solvent to form an extrudable plastic mass, from which small particles, cylinders shape (1mm diameter) of drug / matrix are extruded, chopped into appropriate lengths and converted to spheroids using spheronization equipment. These spheroids are further dried and then film coated with an appropriate polymer to form a film with the desired release patterns. The most widely used excipient in the extruding process is microcrystalline cellulose in its different grades, usually water is used for the wetting process.

Polymers widely used for coating are ethyl cellulose or Eudragit (Ammonio methacrylate copolymer, type A or B). Water soluble ingredients are normally mixed with the ethyl cellulose or with other hydrophobic polymers, such as pore forming agents to assist the control on the drugs release through the hydrophobic coating layer. The water soluble ingredients such as hydroxypropyl cellulose or polyethylene glycol may serve as plasticizers as well.

Venlafaxine Hydrochloride has so far been formulated into a controlled release dosage form with the ability to provide in a single dose a therapeutic blood serum level of the drug over a twenty four hour period. By this method, tighter plasma therapeutic range control can be obtained and a multiple dosing is avoided in this manner. The sharp peaks and troughs in blood plasma drug levels are avoided as well.

With the conventional release dosage forms of Venlafaxine Hydrochloride (tablets), peak blood plasma levels appeared after 2-4 hrs, in contrast to the extended release dosage forms, when plasma levels of Venlafaxine Hydrochloride rose after administration for between five to eight hrs (average – 6) and then begin to fall through a protracted, substantially linear decrease from the peak plasma level for the remainder of the period, maintaining therapeutic level of the drug during the entire twenty four hours period.

In WO 99/22724 (AHP, Sherman) a detailed description of preparing an encapsulated dosage form (coated spheroids) of Venlafaxine Hydrochloride is provided. By the method described therein, a spheroid core is prepared by extruding and spheronizing a mixture of the drug with microcrystalline cellulose, and then coating it with an ethyl cellulose hydroxypropylcellulose mixture.

This dosage form provides an extended release product with the following in vitro dissolution specifications:

Time (hrs)	Average % venlafaxine HCL release
2	<30
4	30-55
8	55-80
12	65-90
24	>80

These dissolution characteristics are pH, RPM independent.

In the present invention an alternative once daily bioequivalent formulation to the innovators one (Effexor XR, described in WO 99/22724) has been developed.

As already mentioned, with high dose water soluble product such as Venlafaxine Hydrochloride (150mg), the usual preferred way of encapsulating it is by preparing and coating an appropriate beads, using the extrusion spheronization process.

In the present invention the microencapsulation has been changed, i.e. is being performed by layering the drug over an inert pareil core, and than coating it with an appropriate polymeric mixture.

The present invention thus consists in an extended release composition comprising as active compound Venlafaxine Hydrochloride, in which Venlafaxine Hydrochloride is coated on a non pareil inert core, which coated core is then coated with a polymeric layer which enables the controlled release of the Venlafaxine Hydrochloride.

The composition preferably comprises 30 – 60% of Venlafaxine Hydrochloride per weight of the total dosage form.

In a preferred embodiment of the present invention, the Venlafaxine Hydrochloride is suitably connected to a binder, said binder may be e.g. polyvinyl pyrrolidone (povidone), hydroxypropylcellulose, hydroxypropylmethylcellulose, etc. The composition preferably comprises 0.5% - 10% of the binder per weight of the total dosage form.

Advantageously the non pareil inert core is an inert sugar core, a microcrystalline cellulose or the like. The composition preferably comprises 30 – 60% of the core per weight of the total dosage form.

Alternatively the drug might be sprayed as it is and the water is then used as binding enhancement agent.

Advantageously the coated core is coated with an isolating/protecting/separating layer, which layer is suitably composed of polymers such as polyvinylpyrrolidone, hydroxypropylcellulose, hydroxypropylmethylcellulose, microcrystallinecellulose, carrageenan, GMS etc. The composition preferably comprises 0.5 – 10% of the isolating layer per weight of the total dosage form.

The core or the isolating layer is coated then with an additional polymeric layer which enables the controlled release of Venlafaxine Hydrochloride. Said additional polymeric layer is composed, e.g. of a hydrophobic polymer mixed with an appropriate hydrophobic plasticizer. Said polymeric layer is suitably sprayed over the coated non pareil layer or over the isolating layer.

Appropriate coating polymers are, e.g. cellulose derivatives such as hydroxypropylmethylcellulose, ethyl cellulose, cellulose acetate, etc. Their suitable plasticizers are, e.g. castor oil, dibutyl sebacate, glyceryl monostearate, diethyl phtalate, glyceryl trihepthanoate etc.

The coating polymeric layer may also be a wax based coating.

The composition preferrably comprises 2 – 15% of the hydrophobic polymer per weight of the total dosage form; and preferably 0.1 – 2% per weight of the hydrophobic plasticizer per weight of the total dosage form.

The above processes are conventional processes that may be performed in a fluid bed coater with a bottom spraying mechanism.

In the composition according to the present invention, preferably not more than 40% of the drug are released after two hours, not more than 60% released after 4 hours and not more than 80% after 8 hours.

The compositions obtained are suitably, e.g. filled into hard gelatin capsules or compressed into tablets.

This formulation has an identical in vitro dissolution profile as Effexor XR (see Sherman, WO99/22724). They are not sensitive to any changes in dissolution conditions. It is bioequivalent to Effexor XR 150 mg caps.

The coating process being used to produce the composition according to the present invention is more efficient than the method being used at the Sherman patent. Moreover, it enables the preparation of the drug in a single type of equipment, e.g. a fluid bed coater.

The present invention will now be illustrated with reference to the following examples without being limited by them.

The process preparing the composition according to the present invention is suitably performed as follows (all temperatures are given in degrees centigrade):

- a. When Venlafaxine Hydrochloride is connected to a binder the Venlafaxine Hydrochloride is connected to the binder by methods know per se.
- b. Stage 1
Coating the non pareil core with the Venlafaxine Hydrochloride (advantageously connected with a binder) is performed at an inlet temperature of $45^{\circ} - 55^{\circ}$ (preferably at 50°) at an outlet temperature of $35^{\circ} - 45^{\circ}$ (preferably at 40°).
At the end of the spraying process, the composition is dried for 10 minutes without nozzle with 30 cfm air flow.
- c. Stage 2
The coated core obtained in Stage 1 is coated with the insulating layer at an inlet temperature of $60^{\circ} \pm 3^{\circ}$ at an outlet temperature of $50^{\circ} \pm 2$.
- d. Stage 3 (when an insulating layer is present in Stage 2)
The core is coated with a further preliminary layer, the conditions of said coating are:
Inlet temp: - $50^{\circ} \pm 2$
Outlet temp: - $40^{\circ} \pm 5$

Example No. 1 (without binder)

Stage 1: <u>Components</u> -	Non pareils 25/30 150gr Venlafaxine Hydrochloride 37.5gr H2O 150gr.
Stage 2: <u>Components</u> --	150gr layered pellets from stage 1 Ethocel 45cp--15gr Methocel 5cp--1gr Ethanol BP 300gr

At the end of the spray process the composition for 10 minutes without nozzle with 30 cfm.

Example No. 2

Stage 1: components –	Non pareils (inert sugar pellets) 150gr Povidone K-30– 3.3gr. Venlafaxine Hydrochloride– 165gr. Ethanol BP– 670gr.
Stage 2: components –	150gr. layered pellets from stage 1 Ethocel 45 cp.– 15gr Methocel 5 cp– 1gr Ethanol BP– 300gr

The coating process was performed in a “4” fluid bed coater made by Coating Place Inc. USA.

Example No. 3:

Stage 1: components –	Non pareils 25/30 – 150gr
	Venlafaxine Hydrochloride 37.5gr
	Povidone K-30– 0.75gr
	Ethanol BP– 160gr
Stage 2: components –	150gr layered pellets from stage 1
	Eudragit RS 30 D– 150gr
	Triethyl citrate– 9gr

Glycerol monostearate- 2.25gr

Polysorbate 80- 1gr

Water- 140gr

The coating process was performed in a "4" fluid bed coater, made by Coating Place Inc. USA.

Example No. 4:

Stage 1: components –	Non-pareils 25/30- 150gr. Povidone K –30- 0.75 gr. Venlafaxine HCL -37.5 gr. Ethanol BP -160gr.
Stage 2: components –	150 gr. pellets from stage 1. Eudragit RS 30D- 150 gr. Eudragit RL 30D- 15 gr. Triethyl citrate- 9 gr. Glycerol monostearate- 2.25 gr. Polysorbate 80-1gr Water- 140 gr.

All processes were performed in a "4" fluid bed coater, made by Coating Place Inc. USA.

Example no.5:

Stage 1: components –	150 gr. Non pareils 25/30 Povidone K – 90 -4.5 gr. Venlafaxine HCL- 150gr. Ethanol BP- 670 gr. Water-110 gr
Stage 2: components –	150 gr. Pellets from stage 1 Povidone K – 30- 3.75 gr. Ethanol absolute -60 gr.
Stage 3: components –	Pellets from stage 2 Ethocel 100 cp.- 8 gr. Dibutyl sebacate- 0.8 gr. Ethanol absolute -300 gr.

CLAIMS

1. An extended release composition comprising as active compound Venlafaxine Hydrochloride, in which Venlafaxine Hydrochloride is coated on a non pareil inert core, which coated core is then coated with a polymeric layer which enables the controlled release of the Venlafaxine Hydrochloride.
2. A composition according to Claim 1, wherein the composition comprises 30 – 60% of Venlafaxine Hydrochloride per weight of the total dosage form.
3. A composition according to Claim 1 or 2, wherein the Venlafaxine Hydrochloride is suitably connected to a binder.
4. A composition according to Claim 3, wherein the binder is selected among polyvinyl pyrrolidone (povidone), hydroxypropylcellulose and hydroxypropylmethylcellulose.
5. A composition according to Claim 3 or 4, wherein the composition comprises 0.5% - 10% of the binder per weight of the total dosage form.
6. A composition according to any of Claims 1 to 5, wherein the non pareil inert core is an inert sugar core, a microcrystalline cellulose or the like.
7. A composition according to any of Claims 1 to 6, which comprises 30 – 60% of the core per weight of the total dosage form.
8. A composition according to any of Claims 1 to 7, wherein the core is coated with an isolating/protecting/separating layer.
9. A composition according to Claim 8, wherein the isolating layer is composed of polymers such as polyvinylpyrrolidone, hydroxypropylcellulose, hydroxypropylmethylcellulose, microcrystalline, cellulose, carrageenan, GMS.
10. A composition according to Claim 8 or 9, wherein the isolating layer is comprised of 0.5 – 10% of the isolating layer per weight of the total dosage form.
11. A composition according to any of Claims 1 to 10, being coated with an additional polymeric layer.
12. A composition according to Claim 11, wherein said additional polymeric layer is composed, e.g. of a hydrophobic polymer mixed with an appropriate hydrophobic plasticizer.

13. A composition according to Claim 12, wherein said coating polymers are selected among cellulose derivatives such as hydroxypropylmethylcellulose, ethyl cellulose, cellulose acetate and their plasticizers are selected among castor oil, dibutyl sebacate, glyceryl monostearate, diethyl phtalate, glyceryl trihepthanoate.
14. A composition according to any of Claims 12 or 13, which comprises 2 – 15% of the hydrophobic polymer per weight of the total dosage form; and 0.1 – 2% per weight of the hydrophobic plasticizer per weight of the total dosage form.

For the Applicant

Dr. Yitzhak Hess & Partners

by:

